



SAMLEX POWER PRODUCTS



IDC Series DC-DC Converters



200 Watts, fully isolated

FEATURES

*Fully Isolated
Short Circuit Protected
Current Limited
2 Year Warranty*

APPLICATIONS

*Earth moving equipment
Heavy trucks
Buses
Marine vehicles
CB radios
12 or 24 Volt lighting systems
AM/FM sound systems*

TECHNICAL SPECIFICATIONS

Model	IDC-200C-12	IDC-200C-24
Input Voltage Range	30 - 60 VDC	30 - 60 VDC
Output Voltage	12.5 VDC	24.5 VDC
Output Current *	16 A	8 A
Input to output isolation	Yes. > 400 V RMS	Yes. > 400 V RMS
Output ripple & noise	< 50 mV RMS	< 50 mV RMS
Peak efficiency	85%	85%
Cooling	By temperature controlled fan	
Operating temperature	- 20° to + 30° C , De-rate linearly to zero at 70° C	
Humidity, non condensing	Max 95%	Max 95%
Protections	Overload / short circuit on the output side Over voltage on the output side Over voltage / transients on the input side Reverse polarity on the input side / Over heating	
Fuse Specs		
External Input Side Fuse (Inline with "Input +" Terminal)	80 V, 10 A	80 V, 10 A
External Output Side Fuse (Inline with "Output +" Terminal)	32 V, 20 A	32 V, 10 A
Wire Size		
Input Wire (up to 6 ft)	AWG # 14	AWG # 14
Output Wire (up to 10 ft)	AWG # 6	AWG # 12
Safety & EMC		
Emission	EN50081-1 / EN61000-6-3	
Immunity	EN50082-1 / EN61000-6-1	
Automotive		
Input/ Output Connections	Quick Connect male 6.3mm / 1/4" flat blade	
Dimensions (L x W x H)	176 x 88 x 50 mm / 6.9" x 3.5" x 1.9"	
Weight	0.6 Kg / 1.4 lbs	

* The output current indicated is the maximum current at the maximum input voltage

Technical Specifications subject to change without notification.

To view a full selection of Samlex products visit our website at www.samlexamerica.com
or contact us: 1 (800) 561-5885 or (604) 525-3836